



ЗОРБА Б

www.zorba-b.mk

ЦЕНОВНИК




HOLTOP

ЗОРБА Б ДОО СКОПЈЕ
ул. Лисец бр. 2-А, Скопје

075300930; 076494012
info@zorba-b.mk
www.zorba-b.mk

HOLTOP

Eco Pair Single Room Energy Recovery Ventilator



Model No.	AV-TTW6-W		
Voltage	100V~240V AC /50-60Hz		
Power [W]	5.9	8.8	11.3
Current [A]	0.03	0.05	0.06
Air flow in regeneration mode [m3/h]	26	55	64
Air flow in energy recovery mode [m3/h]	14	27	32
SFP [W/m3/h]	0.43	0.31	0.35
Sound pressure level at 1 m distance [dBA]	28	32.9	36.7
Sound pressure level at 3 m distance [dBA]	12	27.5	31.9
Regeneration Efficiency	Up to 97%		
SEC	Class A		
Transported air temperature [°C]	-20~50		
Ingress Protection Rating	IP22		
RPM	2000 (max)		
Diameter of duct [mm]	159mm		
Type of installation	Wall mounting		
Net Weight	3.4kg		

Цена со ДДВ 18%

AV-TTW6-W 13,700 ден.

HOLTOP

Wall Mounted

Energy Recovery Ventilator Unit



Airflow (m3/h)	150
Filtration efficiency (%)	99% HEPA
Filtration mode	Pm2.5 purify / Deep purify / Ultra purify
Speed	DC / 8 speed
Input power (W)	35
Temperature efficiency (%)	82
Noise dB(A)	23 – 36
Control	Touch screen panel / Remote control
Air quality display	PM2.5 / Temp & R.H / CO2 Sensor
Operational Mode	Manual / Auto / Timer
Suitable room size (m2)	20 – 45
Dimension (mm)	450*155*660
Weight (kg)	10

Цена со ДДВ 18%

ERVQ-B150-1B1(H01)

36.500 ден.

PM2.5 Filter Version

ERVQ-B150-1B1(H02)

36,500 ден.

CO2 Sensor Version

HOLTOP

CFA Comfort Fresh Air

Wall Mounted Vertical Heat Recovery Ventilator



Comfort Fresh Air

Heat and Energy Recovery Ventilator

FEATURES

- High-efficiency heat recovery up to 95%.
- EC constant airflow fans with low energy consumption, 4 speeds.
- The highest efficiency under all conditions due to Constant Flow Control.
- Supply air purification with primary filter (G4) and medium filter (F7) optional.
- Standard 100% bypass.
- Eco-design A or A+ label.
- Enthalpy exchanger available for a better balanced indoor humidity during winter season.
- The lowest operating noise is 31dB(A).
- Two types of installation to suitable room.
- Smart phone control Android / IOS.

MODEL No.	CFA 250T	CFA 350T	CFA 500T
Voltage [V] / Frequency [Hz]	230V/50Hz		
Airflow [m ³ /h]	250	350	500
External Static Pressure [Pa]	130	150	160
Temperature Efficiency at Rated Airflow [%]	85	85	85
Max Temperature Efficiency [%]	95	95	95
Rated Power [W]	170	320	480
Noise [dB(A)]	35	37	39
Energy Efficiency Class	A	A	A
Weight [kg]	40	40	50



Цена со ДДВ 18%

CFA 350T 85,000 ден.

CFA 500T 92,000 ден.

HOLTOP

CFA Comfort Fresh Air

Ceiling Mounted Energy Recovery Ventilator



CFA150C-1000C



CFA1500C-2000C



Model	Rated Airflow (m³/h)	External Pressure (Pa)	Enthalpy Efficiency (%)		Temperature Efficiency (%)	Noise dB(A)	Voltage (V)	Input Power (W)	N.W. (kg)
			Cooling	Heating					
CFA 500C	500	120	67-82	69-83	78-87	34	220-240	165	33
CFA 650C	650	120	66-81	69-82	77-86	35	220-240	252	38
CFA 800C	800	150	70-81	71-82	79-85	35	220-240	335	48
CFA 1000C	1000	170	71-86	73-87	80-90	37	220-240	420	54

Цена со ДДВ 18%

CFA 500C 59,500 ден.
 CFA 800C 75,500 ден.
 CFA 1000C 87,000 ден.

Model	Rated Airflow (m³/h)	External Pressure (Pa)	Enthalpy Efficiency (%)		Temperature Efficiency (%)	Noise dB(A)	Voltage (V)	Input Power (W)	N.W. (kg)
			Cooling	Heating					
CFA 1500C	1500	175	71-81	72-82	80-85	39	220-240	670	105

Цена со ДДВ 18%

CFA 1500 C 139,000 ден.
 CFA 2000 C 152,000 ден.



HOLTOP

TG/H Series

Energy Recovery Ventilators



Model	XHBQ-D15TG	XHBQ-D20TG	XHBQ-D25TG	XHBQ-D30TG	
Airflow(m ³ /h) L/M/H	1000/1500/1500	1200/2000/2000	2000/2500/2500	2500/3000/3000	
External Static Pressure (Pa) L/M/H	84/135/163	110/132/176	140/170/200	150/180/210	
Enthalpy Exchange Efficiency (%) L/M/H	Cooling	69/66/66	65/62/62	64/61/61	63/60/60
	Heating	74/70/70	73/71/71	72/70/70	71/69/69
Temperature Exchange Efficiency (%) L/M/H	74/71/71	74/71/71	73/70/70	73/70/70	
Noise dB(A) @1.5m below the unit L/M/H	46/49/51	49/51/53	50/52/55	51/54/57	
Power Supply (V/Hz)	220/50	220/50	220/50	220/50	
Current (A)	3.8	4.8	6.3	9.0	
Power Input (W)	785	1020	1300	1950	
Net Weight (Kg)	110	112	130	142	



MODEL	Airflow (m3/h)	ESP (Pa)	Enthalpy Efficiency		Temperature recovery (%)	Noise DE	Rated Voltage (V)	Current (A)	Power (W)	Net Weight (kg)
			Cooler	Heater						
XHEQ-D40H	4000	260	62	69	70	59	380	5.6	2000	240
XHEX-D40H			-	-	72					260
XHEQ-D50H	5000	260	61	64	70	68	380	8.4	3000	300
XHEX-D50H			-	-	72					320
XHEQ-D60H	6000	300	60	62	68	70	380	11.8	4400	355
XHEX-D60H			-	-	69					375

Цена со ДДВ 18%

XHBQ-D15TG 77.500 ден
XHBQ-D20TG 82.500 ден
XHBQ-D25TG 110.000 ден
XHBQ-D30TG 120.000 ден

XHBQ-D40H 142.000 ден
XHBQ-D50H 154.000 ден
XHBQ-D60H 192.000 ден

HOLTOP

THC/DCTHC Series

Energy Recovery Ventilators



Model	Fan Speed	Airflow (m ³ /h)	External pressure (Pa)	Enthalpy Eff.(%)		Temp. Eff. (%)	Noise dB(A)	Current (A)	Input power (W)	N. W. (Kg)
				Summer	Winter					
XHBQ-D6THC	L	500	89	63	67	76	29	0.96	0.20	34
	M	600	92	59	61	70	35			
	H	600	97	59	61	70	39			
XHBQ-D13THC	L	1000	75	58	62	76	38	3.2	0.68	71
	M	1300	85	56	59	70	41			
	H	1300	90	56	59	70	43			

Model	Airflow (m ³ /h)	External pressure (Pa)	Enthalpy Eff.(%)		Temp. Eff. (%)	Noise dB(A)	Voltage (V)	Input power (W)	N. W. (Kg)
			Summer	Winter					
XHBQ-D13DCTHC	1300	90	56-68	59-70	70-83	43	220-240	424	71

Цена со ДДВ 18%

XHBQ-D6THC 39,900 ден.

XHBQ-D13THC 63,500 ден.

XHBQ-D13DCTHC 72.500 ден.

Fresh Air for Your Life



Our aim is to create total air solutions that let you enjoy perfect building air quality.



HOLTOP



Основана во 2002 година во Кина, HOLTOP е водечка компанија специјализирана за производство на опрема за вентилација со рекуперација на топлина.

HOLTOP има 400 вработени и зафаќа површина од повеќе од 70.000 квадратни метри.

Годишниот капацитет на производство на опрема достигнува 200.000 парчиња.

HOLTOP снабдува OEM производи за Midea, LG, Hitachi, McQuay, York, Trane и Carrier

www.holtop.com.cn

ЗОРБА Б ДОО Скопје е увозник за програмата на HOLTOP за Македонија.